



Efficient-Tec International, LLC

Stainless Steel Railing Systems

# Handrail LINEAR FLEX<sup>®</sup>

3 MacAdam ellipse

3 MacAdam ellipse: chromatic stability Control  
 5 color temperature: 2700K, 3000K, 3500K, 4000K, and 6000K  
 CRI>80  
 Medium output 2.93Watts/ft. High output 4.4 Watts/ft  
 Dimmable flexible strip  
 Up to 400 lm/ft.  
 IP67



Linear Flex <sup>®</sup>													
	Color (K)	Bin (±K)	CRI*	lm/ft. (lm)	lm/W (lm)	N° of LEDs/ft	LED Pitch (inch)	Cutting Length (inch)	W/16.4' Reel (W)	Length (feet)	Width (inch)	IP	Product References
<b>Linear Flex-Monocolor IP67</b>													
2.93W/ft.	2700K	50	>80	290 lm	99	26	0.44"	2.8"	48W	16.4'	.39"	67	7260013/80/2K7
	3000K	75		295.9 lm	101								7260013/80/3K
	3500K	100		303.3 lm	104								7260013/80/3K5
	4000K	125		310.6 lm	106								7260013/80/4K
	6000K	200		337 lm	115								7260013/80/6K
4.4 Watts/ft.	2700K	50	>80	386.3 lm	88	37	0.33"	1.97"	72W	16.4'	.39"	67	7260023/80/2K7
	3000K	75		395.1 lm	90								7260023/80/3K
	3500K	100		402.7 lm	92								7260023/80/3K5
	4000K	125		421.4 lm	96								7260023/80/4K
	6000K	200		447.8 lm	102								7260023/80/6K

